

RACK-KVM9150

1U 15" LCD/KEYBOARD DRAWER

Specification

- € **1U chassis drawer with LCD, Keyboard, and touch pad**
- € **Designed for industrial 19" rack mount**
- € **Heavy-duty steel electroplated for chassis**
- € **15.0" TFT LCD Displayer:**
 - 1024x768 (XGA) resolutions
 - 250 cd/m² brightness
 - 50000 hours LCD MTBF
 - 50000 hours backlight lifetime
 - Analog VGA input
- € **Mouse:**
 - Original Logitech® Touch pad (Microsoft mouse compatible with PS/2 mouse interface)
 - Original Logitech® Trackball (optional)
- € **Keyboard:**
 - 105 key ALPS® mechanical key switches Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys
 - English, German, French, Chinese, Japanese version available
- € **Power supply:**
 - 12V DC input (includes universal 100~240V AC input, 12V DC output power supply adapter)
 - 24V/-48V DC input adapter for option
- € **Cable:**

Three in one VGA, keyboard (PS/2), Mouse (PS/2) cable set 1.8M 8 set (3M,6M Optional)
- € **Color:**

Black and ivory color (Colors available for OEM)
- € **Option:**
 - Resistive touch screen
 - 12.1" TFT LCD display
 - 8 ports KVM switch
 - UL-2919 rated 3-in-1 cables set with VGA, keyboard (PS/2), Mouse (PS/2) (1.8M, 3M, 6M Optional)



€ **Dimension:**

- W.19" x D.19.8" x H 1.7" 482mm x D.508mm x H.44mm
- N.W.20 lbs 9KGS, G.W. 24.2 lbs 11KGS, CUFT.2.72

€ **Environment Specification:**

- Operating temperature: 0 ~ 50° C (32 ~ 113° F)
- Relative Humidity: 5~85%
- Vibration: 5~500Hz 1G RMS random vibration

Zeon PDF Driver Trial
www.zeon.com.tw