



SYNERTRON TECHNOLOGY, INC.

14100 E. FIRESTONE BLVD., SANTA FE SPRINGS, CA 90670
TEL: (562) 229 1588 FAX: (562) 229 1558
E-mail: info@synertrontech.com
www.synertrontech.com

Specification



*Heavy-duty steel electroplated for chassis

*Only 1U **4 IN 1** Drawer(KVM switch, KB, LCD, MOUSE)

Keyboard

*105 key English Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys (German, French, Chinese, UK....optional)

Video

*17" TFT LCD Panel

-Panel Resolution 1280x1024

-Input Signal Resolution: 1600x1200, 1280x1024, 1024x768, 800x600, 640x480...(1152x900 for sun-micro system optional)

-Contrast ratio:450:1

-Brightness:300cd/m²

-Display colors:16M

-Built-in 8 languages OSD controls

-Backlight lifetime: 50,000 hrs.

-Automatic flat panel shut-off when monitor is in the closed position, or no signal input.

Mouse

*PS/2 Touchpad (Microsoft mouse compatible with PS/2 mouse interface)

KVM switch

*Up to eight Keyboard/VGA/Mouse inputs (8/16PCS)

*Cascade control up to 120 PCS

*PS/2 and Serial Mouse Emulation Provided for System Bootup

*No software Required-Computer selection Via Hot keys, or OSD(On Screen Display)

*Quick View scan mode for monitoring selected computers

*Hot Pluggable-add or remove computer for maintenance without powering down the switch .

*Scan interval 3~60 sec.

Power Supply:

*System power:12V DC input(Includes universal 100~240V AC input,12V DC output power adapter)

*UL/cUL/TUV/CE/FCC

*(24V/-48V DC input adapter optional)