

RACK-LCD3500

19" Rack-mount 5U LCD Chassis

Specification

- € **0.05" SECC heavy-duty steel electroplated for chassis**
- € **Designed by the lockable door of front panel for protecting the system security**
- € **Designed the anti-vibration card clamp to keep the system stable and safety**
- € **Aluminum handles**
- € **Support AT/ATX form mother board or 14-slot passive back plane**
- € **Display:**
 - ò TFT LCD 10.4"(640x480) /12.1"(800x600)
 - ò Analog VGA input
 - ò LCD On/Off switch
 - ò 50000 hours LCD MTBF
 - ò 50000 hours backlight MTBF
- € **Drive Bays:**
 - ò 1 x 3.5" HDD bay
 - ò 3 x 5.25" bays
- € **Power supply:**
 - ò PS/2 200W ~ 400W power supply
 - ò 250W ~ 350W ATX power supply
- € **VGA Controller Card:** PCI bus, C&T 69000 chipset
- € **Cooling:**
 - ò Built-in two 8cm ball bearing cooling fans
 - ò Power supply fan
- € **One keyboard connector in front panel**
- € **LED Indicator:** Power ON/OFF and Reset switches/ LED indicators at front panel
- € **Speaker:** 8 Ohm,0.4W 1.5"
- € **Chassis Colors:** Black and beige color available, OEM color welcome



€ **Dimension:**

- 19" 483mm (W) x 17.6" 450mm (D) x 8.6" 221mm (H)
- N.W.33 lbs 15KGS, G.W.37.5 lbs17KGS, CUFT: 4.1

€ **Operating Temperature:** 0° ~ 50°C (32 ~ 113° F)

€ **Relative Humidity:** 5~85%

€ **OEM Specification Welcome**

€ **Option:**

- Touch screen built-in
- PCI VGA card for TFT LCD

Zeon PDF Driver Trial
www.zeon.com.tw