

MODEL NO.	Display Size	Active Area	Resolution	Brightness	Contrast Ratio	Response Time	Max Colors	Viewing Angle (U/D/L/R)	Lamp MTBF
IWO-6710-6	6.4"	129.6 x 97.44	640 x 480	300	120:1	30/50	256K	15/35/55/55	20,000
IWO-6710-8	8.4"	170.4 x 127.8	800 x 600	150	250:1	20/30	256K	30/10/40/40	20,000
IWO-6710-8A	8.4"	170.4 x 127.8	800 x 600	220	350:1	10/25	256K	60/40/60/60	20,000
IWO-6710-8C	8.4"	170.4 x 127.8	800 x 600	350	350:1	10/25	256K	60/40/60/60	50,000
IWO-6710-10	10.4"	211.2 x 158.4	800 x 600	150	250:1	20/30	256K	15/35/45/45	20,000
IWO-6710-10A	10.4"	211.2 x 158.4	800 x 600	400	500:1	10/25	256K	40/60/60/60	50,000
IWO-6710-10B	10.4"	211.2 x 158.4	800 x 600	230	500:1	10/25	256K	40/60/60/60	20,000
IWO-6710-12A	12.1"	246 x 184.5	800 x 600	340	300:1	50	256K	20/40/50/50	50,000
IWO-6710-12B	12.1"	246 x 184.5	800 x 600	250	250:1	50/50	256K		50,000
IWO-6710-12C	12.1"	246 x 184.5	1024 x 768	150	250:1	20/30	256K	10/30/40/40	10,000
IWO-6710-15B	15.0"	304.1 x 228.1	1024 x 768	300	500:1	20/5	16.7M	55/65/70/70	50,000
IWO-6710-15D	15.0"	304.1 x 228.1	1024 x 768	500	400:1	5/11	256K	70/80/80/80	50,000
IWO-6710-17A	17.0"	337.9 x 270.3	1280 x 1024	300	450:1	5/11	16.2M	80/80/80/80	50,000
IWO-6710-19	19.0"	376.3 x 301.1	1280 x 1024	250	500:1	15/10	16.7M	85/85/85/85	50,000
IWO-6710-20C	20.1"	376.3 x 301.1	800 x 600	450	500:1	5/11	16.7M	60/60/80/80	50,000
IWO-6710-20D	20.1"	376.3 x 301.1	640 x 480	500	600:1	5/11	16.7M	85/85/85/85	50,000
IWO-6710-30	30.0"		1280 x 768	600	800:1	12	16.7M	85/85/85/85	50,000
						50 vs 50/50	16.7M vs 256K		