

IWO-6710 Panel Mount LCD Monitor Series

Specification

*PANEL-MOUNT TFT LCD monitor. (Analog VGA input.)

*Heavy-duty steel electroplated for chassis.

*6.4", 8.4", 10.4", 12.1", 15", 17", 19", ~40" TFT LCD Monitor

*Resolution 640x480~1600x1200

*8 Languages on Screen Display Function(OSD)

*IP 65 at Aluminum front Panel (Optional)

Power Supply

*12V DC input(includes universal 100~240V AC input, 12V DC output power adapter)

Color

*Available in black. (Colors available for OEM)

Dimensions

IWO-6710-6/8

W.9.8 inch x H.7 inch x D.1.9 inch

W.250mm x H.180mm x D.49mm

IWO-6710-10/12

W.13.3 inch x H.10.1 inch x D.2.1 inch

W.340mm x H.260mm x D.53mm

IWO-6710-15

W.15.7 inch x H.11.8 inch x D.2.1 inch

W.402mm x H.302mm x D.53mm

IWO-6710-17/18

W.17.6 inch x H.14 inch x D.2 inch

W.450mm x H.360mm x D.51mm

IWO-6710-19

W.18.5 inch x H.14.8 inch x D.2 inch

W.475mm x H.380mm x D.51mm

IWO-6710-20

W.20.3 inch x H.15.6 inch x D.2.7 inch

W.520mm x H.400mm x D.70mm

IWO-6710-13 13.3" TFT LCD MONITOR (OEM)

IWO-6710-14 14.1" TFT LCD MONITOR (OEM)

IWO-6710-18 18.0" TFT LCD MONITOR (OEM)

IWO-6710-40 39.6" TFT LCD MONITOR (OEM)

MODEL NO.	Display Size	Active Area	Resolution	Brightness	Contrast Ratio	Response Time	Max Colors	Viewing Angle (U/D/L/R)	Lamp MTBF
IWO-6710-6	6.4"	129.6x97.44	640x480	300	120:1	30/50	262,144	15/35/55/55	20,000
IWO-6710-8	8.4"	170.4x127.8	800x600	150	250:1	20/30	262,144	30/10/40/40	20,000
IWO-6710-8A	8.4"	170.4x127.8	800x600	220	350:1	10/25	262,144	60/40/60/60	20,000
IWO-6710-8C	8.4"	170.4x127.8	800x600	350	350:1	10/25	262,144	60/40/60/60	50,000
IWO-6710-10	10.4"	211.2x158.4	800x600	150	250:1	20/30	262,144	15/35/45/45	20,000

IWO-6710-10A	10.4"	211.2x158.4	800x600	400	500:1	10/25	262,144	40/60/60/60	50,000
IWO-6710-10B	10.4"	211.2x158.4	800x600	230	500:1	10/25	262,144	40/60/60/60	20,000
IWO-6710-12A	12.1"	246x184.5	800x600	340	300:1	50	262,144	20/40/50/50	50,000
IWO-6710-12B	12.1"	246x184.5	800x600	250	250:1	50/50	262,144		50,000
IWO-6710-12C	12.1"	246x184.5	1024x768	150	250:1	20/30	262,144	10/30/40/40	10,000
IWO-6710-15B	15.0"	304.1x228.1	1024x768	300	500:1	20/5	16.7M	55/65/70/70	50,000
IWO-6710-15D	15.0"	304.1x228.1	1024x768	500	400:1	5/11	262,144	70/80/80/80	50,000
IWO-6710-17A	17.0"	337.9x270.3	1280x1024	300	450:1	5/11	16.2M	80/80/80/80	50,000
IWO-6710-19	19.0"	376.3x301.1	1280x1024	250	500:1	15/10	16.7M	85/85/85/85	50,000
IWO-6710-20C	20.1	376.3x301.1	800x600	450	500:1	5/11	16.7M	60/60/80/80	50,000
IWO-6710-20D	20.1	376.3x301.1	640x480	500	600:1	5/11	16.7M	85/85/85/85	50,000
IWO-6710-30	30.0"		1280x768	600	800:1	12	16.7M	85/85/85/85	50,000