

# **DXS220**

## **2 x CV860A-3R10**

### **Processor:**

On-Board VIA Eden 376 PIN EPGA Package  
Front Side Bus 100/133MHz  
VIA C3 Processor 1Ghz  
Integrated Full-Speed 192KB L1/L2 Cache, F.S.B 133MHz

### **System Chipsets:**

MB Chipset: VIA PLE133 with VT8601A and VT82C686B  
VGA: Trident graphics integrated in VIA VT8601A chip  
Sound: VIA VT 1612A AC97 2.2 SOUND  
LAN: 3 x 10/100Mbps Intel LANs

### **Memory:**

PC 133/100 SDRAM DIMM  
One DIMM socket up to 512MB (32M x N type)

### **Graphic:**

Integrated graphics controller with VT8601A Trident VGA  
64-bit single cycle 2D/3D graphic engine  
Supports 2MB to 8MB of frame buffer  
Extended screen resolutions up to 1600x1200x16 bit

### **Sound:**

AC97 2.2 Compliant

### **Power:**

2 x 12V DC-In

### **Back Panel Connectors:**

2 x VGA Connector  
4 x COM Port  
4 x USB 1.1 ports  
6 x LAN Ports  
2 x Parallel ports

**Storage:**

2 x 40-Pin IDE for DOM  
2 x 44-Pin IDE for DOM or 2.5" Slim HDD  
2 x 50-Pin Compact Flash Disk Socket  
2 x DOC (Disk On Chip up to 1GB) Socket

**BIOS:**

Award BIOS  
LAN PXE Boot ROM Support

**OS Support:**

Linux, Windows 9X/2000/XP/CE

**Board Power Consumption:**

12V/2.5A

**Dimension:**

1.7" (H) x 19" (W) x 8.3" (D) or 44.5 (H) x 440 (W) x 210 (D) mm