

DXS241

2 x CV862A-3R53

Processor:

On-Board VIA Eden 376 PIN EPGA Package
Front Side Bus 100/133MHz
VIA Eden Processor 533Mhz
Integrated Full-Speed 192KB L1/L2 Cache, F.S.B 133MHz

System Chipsets:

MB Chipset: VIA PLE133 with VT8601A and VT82C686B
VGA: Trident graphics integrated in VIA VT8601A chip
Sound: VIA VT 1612A AC97 2.2 SOUND
LAN: 3 x 10/100Mbps Intel LANs

Memory:

PC 133/100 SDRAM DIMM
One DIMM socket up to 512MB (32M x N type)

Graphic:

Integrated graphics controller with VT8601A Trident VGA
64-bit single cycle 2D/3D graphic engine
Supports 2MB to 8MB of frame buffer
Extended screen resolutions up to 1600x1200x16 bit

Sound:

AC97 2.2 Compliant

Power:

2 x 12V DC-In

Back Panel Connectors:

2 x VGA Connector
8 x COM Port
4 x USB 1.1 ports
6 x LAN Ports
2 x Parallel ports

Storage:

2 x 40-Pin IDE for DOM
2 x 44-Pin IDE for DOM or 2.5" Slim HDD
2 x 50-Pin Compact Flash Disk Socket
2 x DOC (Disk On Chip up to 1GB) Socket

BIOS:

Award BIOS
LAN PXE Boot ROM Support

OS Support:

Linux, Windows 9X/2000/XP/CE

Board Power Consumption:

12V/2.5A

Dimension:

1.7" (H) x 19" (W) x 8.3" (D) or 44.5 (H) x 440 (W) x 210 (D) mm